

**N 71-15228**

**NASA TECHNICAL  
MEMORANDUM**

**NASA TM X-64554**

**STANDARD DEVIATION OF VERTICAL WIND SHEAR  
IN THE LOWER ATMOSPHERE**

By George H. Fichtl  
Aero-Astroynamics Laboratory

December 17, 1970

**CASE FILE  
COPY**

**NASA**

*George C. Marshall Space Flight Center  
Marshall Space Flight Center, Alabama*



TECHNICAL REPORT STANDARD TITLE PAGE

1. Report No. TMX-64554		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle STANDARD DEVIATION OF VERTICAL WIND SHEAR IN THE LOWER ATMOSPHERE				5. Report Date December 17, 1970	
				6. Performing Organization Code	
7. Author(s) George H. Fichtl				8. Performing Organization Report No.	
9. Performing Organization Name and Address George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812				10. Work Unit No.	
				11. Contract or Grant No.	
				13. Type of Report and Period Covered TECHNICAL MEMORANDUM	
12. Sponsoring Agency Name and Address NASA Washington, D. C. 20546				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract The standard deviation $\sigma$ of vertical two-point longitudinal velocity fluctuation differences is analyzed experimentally with eleven sets of turbulence measurements obtained at the NASA 150-meter ground winds tower site at Cape Kennedy, Florida. It is concluded that the $\sigma/u_{*0}$ is proportional to $(f\Delta z/u_{*0})^{1/3}$ , where the coefficient of proportionality is a function of $f\bar{z}/u_{*0}$ and $u_{*0}/fL_0$ . The quantities $f$ and $L_0$ denote the Coriolis parameter and the surface Monin-Obukhov stability length, respectively; $u_{*0}$ is the surface friction velocity; $\Delta z$ is the vertical distance between the two points over which the velocity difference is calculated; and $\bar{z}$ is the mean height of the mid-point of the interval $\Delta z$ above natural grade. The results of the analysis are valid for $20 < -u_{*0}/fL_0 < 2000$ .					
17. Key Words			18. Distribution Statement PUBLIC RELEASE		
			 E. D. Geissler Director, Aero-Astroynamics Lab.		
19. Security Classif. (of this report) UNCLASSIFIED		20. Security Classif. (of this page) UNCLASSIFIED		21. No. of Pages 25	22. Price \$3.00



# STANDARD DEVIATION OF VERTICAL WIND SHEAR IN THE LOWER ATMOSPHERE

## SUMMARY

The standard deviation  $\sigma$  of vertical two-point longitudinal velocity fluctuation differences is analyzed experimentally with eleven sets of turbulence measurements obtained at the NASA 150-meter ground winds tower site at Cape Kennedy, Florida. It is concluded that the  $\sigma/u_{*0}$  is proportional to  $(f\bar{z}/u_{*0})^{1/3}$ , where the coefficient of proportionality is a function of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . The quantities  $f$  and  $L_0$  denote the Coriolis parameter and the surface Monin-Obukhov stability length, respectively;  $u_{*0}$  is the surface friction velocity;  $\Delta z$  is the vertical distance between the two points over which the velocity difference is calculated; and  $\bar{z}$  is the mean height of the mid-point of the interval  $\Delta z$  above natural grade. The results of the analysis are valid for  $20 < -u_{*0}/fL_0 < 2000$ .

## I. INTRODUCTION

Statistical estimates of wind shear in the planetary boundary layer are important in the design of V/STOL aircraft (vertical/short take-off and landing aircraft). The STOL aircraft are sensitive to variations in lift forces resulting from vertical variations of the horizontal wind during take-off and particularly during landing operations. VTOL aircraft control systems must be designed to counteract extreme tipping moments resulting from vertical variations of the horizontal wind for specified acceptable values of risk of exceeding the design wind shear conditions. Similarly, wind shear information will also be necessary in the design of the forthcoming NASA Space Shuttle for both the launch and landing phases. During the launch phase the Shuttle will experience tipping moments; during the landing phase, it will experience fluctuating lift forces. The vertical two-point longitudinal velocity differences that will be experienced by these vehicles can be divided into two parts: the wind shear resulting from the mean flow, and the fluctuating or random part resulting from turbulence. The mean shear can be calculated with currently available models of the mean flow wind profile in the atmospheric boundary layer [1,2, and 3]. However, the fluctuating part must be specified statistically for engineering problems, and this requires knowledge about the statistical moments or the distribution function of the shear. A great deal of information can be gained by studying the second moment of wind shear. In addition, the square root of the second

moment, the standard deviation, of a random variable is used as a standardizing parameter to render the random variable nondimensional. Accordingly, the analysis in this report is restricted to an examination of the second moment of vertical two-point longitudinal velocity differences, or, in other words, wind shear.

It is hypothesized that the standard deviation of the wind shear scaled with the surface friction velocity  $u_{*0}$  is a universal function of the nondimensional parameters  $f\Delta z/u_{*0}$ ,  $f\bar{z}/u_{*0}$ , and  $u_{*0}/fL_0$ , where  $f$  is the Coriolis parameter,  $L_0$  is the surface Monin-Obukhov length,  $\Delta z$  is the vertical distance between the two points over which the shear is calculated, and  $\bar{z}$  is the mean height of the mid-point of the shear interval  $\Delta z$  above natural grade.

From the eleven cases of turbulence in unstable air selected for analysis, it is concluded that  $\sigma/u_{*0}$  is indeed a function of the nondimensional parameters listed above. Empirical mathematical expressions are obtained to represent this function. It appears that  $\sigma/u_{*0}$  is proportional to  $(f\Delta z/u_{*0})^{1/3}$ , the coefficient of proportionality being a function of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . The results of the analysis are valid for  $20 < -u_{*0}/fL_0 < 2000$ .

The author expresses his thanks to Mr. Archie Jackson and Mrs. Ella Mae McAllister of the Marshall Space Flight Center's Computation Laboratory. Mr. Jackson developed the program for the calculation of the two-point standard deviations. Mrs. McAllister developed the remaining programs which were used to calculate the non-dimensional quantities. In addition, thanks go to Mr. Julian Nelson and Mr. Douglas Mackiernan of the Aero-Astrodynamic Laboratory for their help in the preparation of this report and the analysis of the data.

## II. THE DATA SOURCE

The data analyzed in this report consist of eleven sets of longitudinal turbulent velocity fluctuation time histories digitized at 0.2-second intervals with 18,000 data points per time history. The longitudinal velocity fluctuations were calculated with horizontal wind speed and direction data measured at the 18-, 30-, 60-, 90-, 120-, and 150-meter levels at the NASA meteorological tower site at the Kennedy Space Center with Climet (model C1-14) wind sensors. The measurements were taken during the daytime in unstable air. The computation procedures used to calculate the longitudinal turbulent velocity fluctuations are discussed by Fichtl and McVehil in reference 4. Supporting temperature measurements were made at the 18- and 30-meter levels with Climet (model C1-016) aspirated thermocouples. (Details concerning the instrumentation at the NASA tower site can be found in a report by Kaufman and Keene [5]; the surface roughness lengths associated with this site are discussed by Fichtl and McVehil in reference 4.)

### III. THEORETICAL CONSIDERATIONS

The instantaneous longitudinal velocity  $u(x,y,z,t)$  in a horizontally homogeneous atmospheric boundary layer can be represented as

$$u(x,y,z,t) = \bar{u}(z) + u'(x,y,z,t), \quad (1)$$

where  $\bar{u}(z)$  is the temporal mean wind at height  $z$ , and  $u'(x,y,z,t)$  is a longitudinal turbulent velocity fluctuation. Upon evaluating equation (1) at heights  $z_1$  and  $z_2$  ( $z_2 > z_1$ ) for fixed values of  $x,y$ , and  $t$ , we may calculate the two-point velocity difference

$$\Delta u(z_1, z_2, t) = \Delta \bar{u}(z_1, z_2) + \Delta u'(z_1, z_2, t), \quad (2)$$

where

$$\Delta u(z_1, z_2, t) = u(z_2, t) - u(z_1, t) \quad (3)$$

$$\Delta \bar{u}(z_1, z_2) = \bar{u}(z_2) - \bar{u}(z_1) \quad (4)$$

$$\Delta u'(z_1, z_2, t) = u'(z_2, t) - u'(z_1, t). \quad (5)$$

The dependence of  $\Delta u$  and  $\Delta u'$  on  $x$  and  $y$  is understood. For engineering purposes, the quantity  $\Delta \bar{u}(z_1, z_2)$  can be treated as a known quantity that can be calculated with a power law wind profile like

$$\bar{u}(z) = \bar{u}(z_1) (z/z_1)^\alpha, \quad (6)$$

where  $\alpha$  is a positive constant, or with the more elegant wind profile formulations for the barotropic and baroclinic Ekman planetary boundary layers by Blackadar [1]. For values of  $z_2 \lesssim 30$  m, the mean wind profile law appropriate for a Monin layer can be used:

$$\bar{u}(z) = \frac{u_{*0}}{k_1} \left( \ln \frac{z}{z_0} - \psi(z/L_0) \right), \quad (7)$$

where  $u_{*0}$  and  $L_0$  denote the surface friction velocity and Monin-Obukhov stability length,  $z_0$  is the surface roughness length,  $k_1$  is von Karman's

constant with numerical value approximately equal to 0.4 and  $\psi(z/L_0)$  is a universal function of  $z/L_0$  [3]. On the other hand, the quantity  $\Delta u'(z, z_2, t)$  is a rapidly varying random function of time, and thus must be treated statistically.

The longitudinal time histories were differenced in the vertical to yield fifteen longitudinal velocity difference time histories for each case. Unbiased estimates of the second moment were calculated with the formula

$$\sigma^2 = \frac{1}{n-1} \sum_{i=1}^n (\Delta u'_i)^2, \quad (8)$$

where  $\sigma$  is the standard deviation of the random longitudinal shear and  $n$  is the number of data points used in the calculation.

#### IV. DIMENSIONAL ANALYSIS

The Monin-Obukhov similarity hypothesis [3] predicts that the standard deviation of two-point longitudinal velocity differences, scaled with the surface friction velocity  $u_{*0}$ , are universal functions of  $z_1/L_0$  and  $z_2/L_0$  or  $\bar{z}/L_0$  and  $\Delta z/L_0$ , where

$$\bar{z} = \frac{z_1 + z_2}{2} \quad (9)$$

$$\Delta z = z_2 - z_1$$

Thus, the Monin-Obukhov similarity hypothesis leads to the conclusion that

$$\sigma/u_{*0} = F(\bar{z}/L_0, \Delta z/L_0), \quad (10)$$

where  $F$  is a universal function of  $\bar{z}/L_0$  and  $\Delta z/L_0$ . However, as one proceeds upward out of the Monin layer into the Ekman layer, it is reasonable to hypothesize the  $\sigma/u_{*0}$  is a function of  $\bar{z}/L_0$ ,  $\Delta z/L_0$  and other parameters that characterize the action of Coriolis forces and baroclinic effects. Blackadar and Tennekes [6] have shown that, in the horizontally

homogeneous, neutral, barotropic Ekman layer,  $u_{*0}/f$  is the appropriate length scale, where  $f$  is the Coriolis parameter. This result was produced by analyzing the mean flow momentum conservation equations along with the turbulent energy equation. Thus, as a working hypothesis, one might assume that  $\sigma/u_{*0}$  is a function of the independent variables

$$\Delta z, \bar{z}, L_0, u_{*0}/f. \quad (11)$$

According to Buckingham's theorem [7], the number of independent non-dimensional quantities that can be constructed from this list of variables is three. Now there are eighteen possible ways to select this group of three independent nondimensional quantities such that  $\bar{z}$  and  $\Delta z$  appear within each group. However, any one of the possible groups can be derived from the remaining seventeen groups. Accordingly, we are free to select any one group we like to perform a data analysis; thus, we hypothesize that

$$\frac{\sigma}{u_{*0}} = F \left( \frac{f\Delta z}{u_{*0}}, \frac{f\bar{z}}{u_{*0}}, \frac{u_{*0}}{fL_0} \right). \quad (12)$$

This hypothesis includes the dominant effects in the Ekman layer: atmospheric stability, and the action of Coriolis forces in the horizontal mean flow momentum conservation equations. It does not include baroclinic effects resulting from a height-dependent horizontal pressure-gradient force. Nevertheless, the hypothesis given by equation (12) seems to be appropriate in view of the fact that the outstanding feature of the Ekman layer is the action of Coriolis forces and that inclusion of baroclinic effects will only lead to refinements. This hypothesis will be used to analyze the standard deviation of vertical two-point longitudinal velocity fluctuation differences. The procedures used in the calculation of  $u_{*0}$  and  $L_0$  are given in appendix A. The data used in these calculations and the results of the calculations are given in appendix B.

## V. DATA ANALYSIS

To estimate the universal function  $F$  on the right-hand side of equation (12), the nondimensional standard deviation  $\sigma/u_{*0}$  was plotted as a function of  $f\Delta z/u_{*0}$  for various categories of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . Each case is characterized by a single value of  $u_{*0}/fL_0$ ; however, within each case, the quantity  $f\bar{z}/u_{*0}$  can vary.

Figure 1 is a plot of  $\sigma/u_{*0}$  as a function of  $f\Delta z/u_{*0}$  for the various categories of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . The data appear to show that, for each of the selected categories,  $\sigma/u_{*0}$  is proportional to  $(f\Delta z/u_{*0})^{1/3}$ . In addition, within each category of  $f\bar{z}/u_{*0}$ , the values of  $\sigma/u_{*0}$  tend to sort out according to the parameter  $u_{*0}/fL_0$ ; i.e., for fixed values  $f\bar{z}/u_{*0}$  and  $f\Delta z/u_{*0}$ , the quantity  $\sigma/u_{*0}$  tends to be a decreasing function of  $-u_{*0}/fL_0$ . There also appears to be a dependence of  $\sigma/u_{*0}$  on  $f\bar{z}/u_{*0}$ ; i.e., for fixed values of  $f\Delta z/u_{*0}$  and  $u_{*0}/fL_0$ , the quantity  $\sigma/u_{*0}$  is a decreasing function  $f\bar{z}/u_{*0}$ .

To see these effects better, it was assumed that  $\sigma/u_{*0}$  is proportional to  $(f\Delta z/u_{*0})^{1/3}$  for all categories of the remaining independent variables, so that

$$\frac{\sigma}{u_{*0}} = G\left(\frac{f\bar{z}}{u_{*0}}, \frac{u_{*0}}{fL_0}\right) \left(\frac{f\Delta z/u_{*0}}{0.001}\right)^{1/3}, \quad (13)$$

where  $G$  is a universal function of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . The function  $G$  was determined by fitting equation (13) to the data in figure 1 for each category of  $f\bar{z}/u_{*0}$  and  $u_{*0}/fL_0$ . The results of these calculations are shown in figure 2. We see from this figure that  $G$  and thus  $\sigma/u_{*0}$  are clearly decreasing functions of  $f\bar{z}/u_{*0}$  and increasing functions of  $u_{*0}/fL_0$ .

To give the experimental results mathematical expression, we assume that the curves in figure 2 are shape-invariant with respect to variation in  $u_{*0}/fL_0$  and that translation only with respect to the  $G$ -axis is required to produce a collapse of these curves. This means that there exists a function  $H(u_{*0}/fL_0)$  such that

$$G\left(\frac{f\bar{z}}{u_{*0}}, \frac{u_{*0}}{fL_0}\right) = G\left(\frac{f\bar{z}}{u_{*0}}, -150\right) + H\left(\frac{u_{*0}}{fL_0}\right). \quad (14)$$

In view of the experimental results in figure 2, these assumptions appear to be reasonable. To calculate the function  $H(u_{*0}/fL_0)$ , we subtract the experimental estimate of  $G(f\bar{z}/u_{*0}, -150)$  from each curve in figure 2 and then average each of the resulting difference functions over the experimental range of variation  $f\bar{z}/u_{*0}$ . The experimental estimates of  $H(u_{*0}/fL_0)$  for the various values of  $u_{*0}/fL_0$  are given in figure 3. The function

$$H(u_{*0}/fL_0) = -0.072 \ln\left(-\frac{u_{*0}/fL_0}{150}\right) \quad (15)$$

appears to summarize these results reasonably well. To improve our estimate of  $G(f\bar{z}/u_{*0}, -150)$ , we subtract  $H(u_{*0}/fL_0)$  as given by equation (15) from the experimental values of  $G(fz/u_{*0}, u_{*0}/fL_0)$  given in figure 2 and average the resulting difference functions over the experimental range of variation of  $u_{*0}/fL_0$  for each category of  $f\bar{z}/u_{*0}$ . The revised estimate of the function  $G(f\bar{z}/u_{*0}, -150)$  is depicted in figure 4, and the analytical expression

$$G(f\bar{z}/u_{*0}, -150) = 1 + 2.77 \left( \frac{f\bar{z}/u_{*0}}{0.001} \right)^{-5/2} \quad (16)$$

summarizes these data. The results in figure 4 show that  $G(f\bar{z}/u_{*0}, -150) \rightarrow 1$  as  $f\bar{z}/u_{*0} \rightarrow \infty$ . This means that  $\sigma/u_{*0}$  becomes asymptotically height-invariant as  $f\bar{z}/u_{*0} \rightarrow \infty$ . The function (16) contains this asymptotic behavior.

The combination of equations (13) through (15) yields

$$\frac{\sigma}{u_{*0}} = \left[ 1 + 2.77 \left( \frac{f\bar{z}/u_{*0}}{0.001} \right)^{-5/2} - 0.072 \ln \left( - \frac{u_{*0}/fL_0}{150} \right) \right] \left( \frac{f\Delta z/u_{*0}}{0.001} \right)^{1/3} \quad (17)$$

According to equation (17)  $\sigma/u_{*0}$  becomes large as  $f\bar{z}/u_{*0} \rightarrow 0$  and  $f\Delta z/u_{*0} \rightarrow \infty$ . This means that  $\sigma$  becomes large as the height  $\bar{z}$  decreases and the interval  $\Delta z$  increases. In addition,  $\sigma/u_{*0}$  decreases as  $-u_{*0}/fL_0$  increases. However, equation (17) predicts that  $\sigma/u_{*0} < 0$  at sufficiently large values of  $-u_{*0}/fL_0$ . This is nonsense and is an apparent shortcoming of the empirical formula (17). Negative values of  $\sigma/u_{*0}$  are predicted with (17) when

$$f\bar{z}/u_{*0} > 0.001 \left[ \frac{2.77}{0.072 \ln \left( - \frac{u_{*0}/fL_0}{150} \right) - 1} \right]^{2/5}, \quad (18)$$

provided  $-u_{*0}/fL_0 > 4 \times 10^8$ . However, values of  $-u_{*0}/fL_0 > 4 \times 10^8$  are very rare if we exclude the region of the earth on and about the equator. A physically realizable upper bound value on  $-u_{*0}/fL_0$  in unstable air is probably on the order of 10,000 if we exclude the equatorial region of

the earth. Thus, the shortcoming of predicting negative values of  $\sigma/u_{*0}$  with equation (17) is only apparent and would not arise in practical situations. The function  $H(u_{*0}/fL_0)$  probably tends to approach a constant value as  $-u_{*0}/fL_0$  becomes large and if this occurs in the interval  $1,000 < -u_{*0}/fL_0 < 10,000$ , then the error in the estimate of  $\sigma/u_{*0}$  resulting from (17) is approximately 5 percent. As  $-u_{*0}/fL_0 \rightarrow 0$  from positive values of  $-u_{*0}/fL_0$ ,  $\sigma/u_{*0} \rightarrow \infty$ . The function  $H(u_{*0}/fL_0)$  should approach a finite value as  $-u_{*0}/fL_0 \rightarrow 0$  because of the finite nature of  $\sigma$ . Accordingly,  $H(u_{*0}/fL_0)$  does not have logarithmic behavior as  $-u_{*0}/fL_0 \rightarrow 0$  as predicted by (15). The precise value of  $-u_{*0}/fL_0$  where  $H(u_{*0}/fL_0)$  departs from the behavior stated by (15) can only be determined with measurements of  $\sigma/u_{*0}$  associated with values of  $-u_{*0}/fL_0 < 20$ . In view of these comments, it is recommended that (17) be used to obtain estimates of  $\sigma$  only for those situations in which  $u_{*0}/fL_0$  is contained within the experimental range of variation in this report, i.e.,  $20 \leq -u_{*0}/fL_0 \leq 2,000$ . Estimates of  $\sigma/u_{*0}$  can be obtained with equation (17) for  $2,000 < -u_{*0}/fL_0 < 10,000$  which probably have errors equal to 5 percent.

The correlation coefficient of the longitudinal wind fluctuations at  $z_1$  and  $z_2$  is

$$R(u'(z_1), u'(z_2)) = \frac{\sigma_u^2(z_1) + \sigma_u^2(z_2) - \sigma^2(z_1, z_2)}{2\sigma_u(z_1) \sigma_u(z_2)}, \quad (19)$$

where  $\sigma_u(z)$  is the standard deviation of the longitudinal wind fluctuations at height  $z$ . Fichtl and McVehil [4] find that for the unstable boundary layer

$$\frac{\sigma_u}{u_{*0}} = 1.9(z/18)^{-0.14}. \quad (20)$$

This result was obtained by effectively averaging together measurements of  $\sigma_u/u_{*0}$  obtained during various degrees of instability in the first 150 m of the atmospheric boundary layer at Cape Kennedy, Florida. However, the recent results of Panofsky and Mirabella [9] appear to show that  $\sigma_u/u_{*0}$  is relatively insensitive to changes in stability and thus  $u_{*0}/fL_0$ . Now, (20) shows that  $\sigma_u/u_{*0}$  is a slowly varying function of  $z$  so that we will assume  $\sigma_u(z_1) \simeq \sigma_u(z_2)$  and set  $\sigma_u/u_{*0} = 1.5$ . This value of  $\sigma/u_{*0}$  occurs at  $z \simeq 80$  m. Thus, we may write (19) as

$$R(u'(z_1), u'(z_2)) \simeq 1 - \frac{(\sigma/u_{*0})^2}{4.5}. \quad (21)$$

We may conclude from (17) and (21) that in the unstable boundary layer the interlevel correlation coefficient of the longitudinal velocity fluctuations increases as the instability of the boundary layer and  $f\bar{z}/u_{*0}$  increase and as  $f\Delta z/u_{*0}$  decreases.

## VI. CONCLUDING COMMENTS

1. We have experimentally analyzed the standard deviation of vertical two-point longitudinal velocity fluctuation differences, and have found that  $\sigma/u_{*0}$  is indeed a function of  $f\bar{z}/u_{*0}$ ,  $f\Delta z/u_{*0}$ , and  $u_{*0}/fL_0$ . In particular,  $\sigma/u_{*0}$  is proportional to  $(f\Delta z/u_{*0})^{1/3}$ . Although the analysis did not include baroclinic effects, we believe them to be of second order. The fact that  $\sigma^2$  is proportional to  $(\Delta z)^{2/3}$  is, in all likelihood, related to the fact that the structure function of longitudinal velocity fluctuations at a given height is proportional to  $(\Delta x)^{2/3}$  for sufficiently small values of the horizontal space lag  $\Delta x$  when an inertial subrange is present. The precise nature of this relationship is not obvious; however, it will be the subject of future investigation by the author.

2. This study is the first part of a four-part study to define the statistical properties of fluctuating wind shears in the atmospheric boundary layer. The second part of the study will be concerned with determining the dependence of the third and fourth moments,  $\mu_3$  and  $\mu_4$ , on  $f\Delta z/u_{*0}$ ,  $f\bar{z}/u_{*0}$ , and  $u_{*0}/fL_0$  in unstable air. The third part will be concerned with determining a class of distribution functions which contain four parameters that will adequately describe the observed wind shear distribution functions in unstable air. Preliminary results appear to show that the Pearson system of distribution functions can be used to represent the data. The four parameters which will appear in the distribution function will be completely specified upon specifying the first four moments of the wind shear. The data in this report will be used in parts two and three of the total study. The fourth part will be concerned with extending the results of parts one, two, and three to (1) the neutral boundary layer with turbulence data for relatively high wind speed conditions ( $\bar{u}(18m) \geq 15 \text{ m sec}^{-1}$ , say) and (2) stable boundary layers associated with nighttime conditions. Accordingly, the overall goal is to develop models of  $\sigma$ ,  $\mu_3$  and  $\mu_4$  such that these parameters can be calculated for given values of the height parameters  $\bar{z}$  and  $\Delta z$  once the external parameters  $L_0$ ,  $u_{*0}$ , and  $f$  are specified. Substitution of  $\sigma$ ,  $\mu_3$ ,  $\mu_4$  and the mean wind shear (see section III) into the distribution function of wind shear will facilitate the calculation of wind shear for any percentile level of occurrence for a given state of the boundary layer. Furthermore, the model will permit climatological studies of wind shear with rather straightforward statistical procedures for specified locations upon specifying

the climatological statistics of  $L_0$  and  $u_{*0}$  (joint distribution function). The distribution function of these external parameters could be extracted from standard meteorological observations.




Figure 1. Experimental values of  $\sigma/u_{*0}$  for various categories of  $f\bar{z}/u_{*0}$  and  $-u_{*0}/fL_0$




Figure 2. Estimate of the function  $G(fz/uz, uz/fL_0)$




Figure 3. Estimate of the function  $H(u^*_0/fL_0)$




Figure 4. Estimate of the function  $G(fz/uz, -150)$

## APPENDIX A

### Calculations of the Scaling Parameters $u_{*0}$ and $L_0$

In the unstable Monin layer, the dimensionless mean flow shear is a universal function of  $z/L_0$ , so that

$$\frac{k_1 z}{u_{*0}} \frac{\partial \bar{u}}{\partial z} = \phi_u(z/L_0), \quad (\text{A-1})$$

where  $\bar{u}(z)$  is the mean wind speed at height  $z$ ,  $k_1$  is von Karman's constant with numerical value approximately equal 0.4,  $u_{*0}$  is the surface friction velocity, and  $\phi_u(z/L_0)$  is a universal function of  $z/L_0$ . The quantity  $L_0$  is the surface Monin-Obukhov stability length, namely,

$$L_0 = - \frac{u_{*0}^3 C_p \bar{\rho} \bar{T}}{k_1 g H_0}. \quad (\text{A-2})$$

In this equation  $H_0$  is the surface heat flux,  $\bar{\rho}$  and  $\bar{T}$  denote the mean flow density and Kelvin temperature,  $g$  is the acceleration of gravity, and  $C_p$  is the specific heat at constant pressure. The dimensionless shear  $\phi_u$  is related to the flux Richardson number through the experimentally derived relationship

$$\phi_u = (1 - 18Ri)^{1/4}, \quad (\text{A-3})$$

which is given in reference 3. The flux Richardson number is defined as

$$Ri = \frac{\frac{g}{\bar{\theta}} \frac{\partial \bar{\theta}}{\partial z}}{(\partial \bar{u} / \partial z)^2}, \quad (\text{A-4})$$

where  $\bar{\theta}$  is the mean potential temperature at height  $z$ . The flux Richardson number is a function of  $z/L_0$ . We shall invoke the Businger hypothesis [8] to relate  $Ri$  to  $z/L_0$ , so that

$$Ri = z/L_0. \quad (\text{A-5})$$

Upon combining equations (A-1), (A-3), and (A-5) and integrating the resulting relationship, we find that

$$\bar{u}(z) = \frac{u_{*0}}{k_1} \left\{ \ln \frac{z}{z_0} - \psi\left(\frac{z}{L_0}, \frac{z_0}{L_0}\right) \right\}, \quad (\text{A-6})$$

where

$$\psi\left(\frac{z}{L_0}, \frac{z_0}{L_0}\right) = \int_{-z_0/L_0}^{-z/L_0} \frac{1 - (1 + 18\xi)^{-1/4}}{\xi} d\xi. \quad (\text{A-7})$$

We have used the condition that  $\bar{u}(z_0) = 0$  in the derivation of (A-6), where  $z_0$  is the surface roughness length. Equation (A-7) can be evaluated numerically for any value of  $z/L_0$ . The lower bound of this integral may be set equal to zero because the contribution to  $\psi$  from the region  $0 < -z/L_0 < -z_0/L_0$  is negligibly small.

Equations (A-4) through (A-7) can be used to calculate the scaling velocity  $u_{*0}$  and  $L_0$ . The procedure for calculating these quantities is as follows: (1) calculate the gradient Richardson number, equation (A-4), with the mean flow wind and potential temperature profile data in the Monin layer, (2) calculate  $L_0$  with equation (A-5), and finally (3) calculate  $u_{*0}$  with (A-6) and (A-7).

The 18- and 30-meter temperature and wind data were used to estimate the Richardson number. The distributions of  $\bar{u}(z)$  and  $\bar{\theta}(z)$  between the 18- and 30-meter levels were assumed to be logarithmic profiles. The expressions for  $\bar{u}(z)$  and  $\bar{\theta}(z)$  were differentiated with respect to  $z$  and evaluated at the geometric height  $z = 23$  meters to yield estimates of  $\partial\bar{u}/\partial z$  and  $\partial\bar{\theta}/\partial z$  for the calculation of  $Ri$ . This Richardson number was used to calculate  $L_0$  in step (2) above. The 18-meter level wind speed and  $\psi(18m/L_0)$  were used to calculate  $u_{*0}$  in step (3).

The surface roughness lengths  $z_0$  that were associated with the NASA 150-meter meteorological tower site and that were used in the calculation of  $u_{*0}$  are given in reference 4.

## APPENDIX A

### Calculations of the Scaling Parameters $u_{*0}$ and $L_0$

In the unstable Monin layer, the dimensionless mean flow shear is a universal function of  $z/L_0$ , so that

$$\frac{k_1 z}{u_{*0}} \frac{\partial \bar{u}}{\partial z} = \phi_u(z/L_0), \quad (\text{A-1})$$

where  $\bar{u}(z)$  is the mean wind speed at height  $z$ ,  $k_1$  is von Karman's constant with numerical value approximately equal 0.4,  $u_{*0}$  is the surface friction velocity, and  $\phi_u(z/L_0)$  is a universal function of  $z/L_0$ . The quantity  $L_0$  is the surface Monin-Obukhov stability length, namely,

$$L_0 = - \frac{u_{*0}^3 C_p \bar{\rho} \bar{T}}{k_1 g H_0}. \quad (\text{A-2})$$

In this equation  $H_0$  is the surface heat flux,  $\bar{\rho}$  and  $\bar{T}$  denote the mean flow density and Kelvin temperature,  $g$  is the acceleration of gravity, and  $C_p$  is the specific heat at constant pressure. The dimensionless shear  $\phi_u$  is related to the flux Richardson number through the experimentally derived relationship

$$\phi_u = (1 - 18Ri)^{1/4}, \quad (\text{A-3})$$

which is given in reference 3. The flux Richardson number is defined as

$$Ri = \frac{\frac{g}{\bar{\theta}} \frac{\partial \bar{\theta}}{\partial z}}{(\partial \bar{u} / \partial z)^2}, \quad (\text{A-4})$$

where  $\bar{\theta}$  is the mean potential temperature at height  $z$ . The flux Richardson number is a function of  $z/L_0$ . We shall invoke the Businger hypothesis [8] to relate  $Ri$  to  $z/L_0$ , so that

$$Ri = z/L_0. \quad (\text{A-5})$$

Upon combining equations (A-1), (A-3), and (A-5) and integrating the resulting relationship, we find that

$$\bar{u}(z) = \frac{u_{*0}}{k_1} \left\{ \ln \frac{z}{z_0} - \psi\left(\frac{z}{L_0}, \frac{z_0}{L_0}\right) \right\}, \quad (\text{A-6})$$

where

$$\psi\left(\frac{z}{L_0}, \frac{z_0}{L_0}\right) = \int_{-z_0/L_0}^{-z/L_0} \frac{1 - (1 + 18\xi)^{-1/4}}{\xi} d\xi. \quad (\text{A-7})$$

We have used the condition that  $\bar{u}(z_0) = 0$  in the derivation of (A-6), where  $z_0$  is the surface roughness length. Equation (A-7) can be evaluated numerically for any value of  $z/L_0$ . The lower bound of this integral may be set equal to zero because the contribution to  $\psi$  from the region  $0 < -z/L_0 < -z_0/L_0$  is negligibly small.

Equations (A-4) through (A-7) can be used to calculate the scaling velocity  $u_{*0}$  and  $L_0$ . The procedure for calculating these quantities is as follows: (1) calculate the gradient Richardson number, equation (A-4), with the mean flow wind and potential temperature profile data in the Monin layer, (2) calculate  $L_0$  with equation (A-5), and finally (3) calculate  $u_{*0}$  with (A-6) and (A-7).

The 18- and 30-meter temperature and wind data were used to estimate the Richardson number. The distributions of  $\bar{u}(z)$  and  $\bar{\theta}(z)$  between the 18- and 30-meter levels were assumed to be logarithmic profiles. The expressions for  $\bar{u}(z)$  and  $\bar{\theta}(z)$  were differentiated with respect to  $z$  and evaluated at the geometric height  $z = 23$  meters to yield estimates of  $\partial\bar{u}/\partial z$  and  $\partial\bar{\theta}/\partial z$  for the calculation of  $Ri$ . This Richardson number was used to calculate  $L_0$  in step (2) above. The 18-meter level wind speed and  $\psi(18m/L_0)$  were used to calculate  $u_{*0}$  in step (3).

The surface roughness lengths  $z_0$  that were associated with the NASA 150-meter meteorological tower site and that were used in the calculation of  $u_{*0}$  are given in reference 4.

APPENDIX B

Wind Speed and Temperature Profile Data and Other Parameters

The wind profile and temperature data that were used in this report are given in Tables B-1 and B-2. The 18-meter level wind direction is tabulated here because the surface roughness length at the NASA 150-meter tower facility is a function of wind direction. The values of  $Ri(23\text{ m})$ ,  $L_0$ , and  $u_{*0}$  that were calculated with these data are given in Table B-3.

TABLE B-1

Table of Temperature Profile Data\*  
(Temperature in °F)

Case No.	Date	Time (EST)	T(3m)	$(\Delta T)_1$	$(\Delta T)_2$
299	1/23/68	1315-1400	76.0	-1.41	-1.73
305	1/26/68	1130-1230	52.4	-2.19	-2.66
310	2/8/68	915-1015	40.5	- .32	-1.82
319	2/26/68	1030-1130	59.0	-1.28	-2.63
355	3/20/68	1330-1430	75.0	-1.82	-2.21
365	3/28/68	905-932	73.5	-1.44	-2.42
366	3/28/68	1145-1245	74.5	-2.63	-3.13
406	4/7/68	1507-1537	79.0	-2.02	-2.57
445	5/7/68	1400-1415	78.2	-2.29	-2.54
551	6/29/68	947-1027	79.8	- .93	-1.90
554	6/30/68	933-952	83.1	-1.40	-1.91

\*  $(\Delta T)_1 = T(18\text{m}) - T(3\text{m})$ .

$(\Delta T)_2 = T(30) - T(3\text{m})$ .

TABLE B-2

Table of Wind Speed and Direction Data

Case No.	18 m Wind Direction	$\bar{u}(18 \text{ m})$ (m sec <sup>-1</sup> )	$\bar{u}(30 \text{ m})$ (m sec <sup>-1</sup> )
299	219°	5.95	7.55
305	338°	8.50	9.31
310	298°	9.98	11.34
319	320°	4.81	5.13
355	83°	3.87	4.13
365	95°	4.98	5.25
366	87°	6.12	6.48
406	71°	4.36	4.73
445	93°	9.62	10.34
551	34°	2.92	3.05
554	86°	4.01	4.12

TABLE B-3

Table of Boundary Layer Parameters

Case No.	Ri(23 m)	L <sub>0</sub> (m)	u <sub>*0</sub> (m sec <sup>-1</sup> )
299	-0.065	-357	0.52
305	-0.090	-259	0.76
310	-0.032	-716	1.20
319	-2.448	- 9	0.48
355	-0.557	- 42	0.36
365	-2.234	- 10	0.67
366	-0.504	- 46	0.56
406	-0.546	- 43	0.40
445	-0.234	- 99	0.98
551	-8.977	- 3	0.41
554	-5.100	- 5	0.49

## REFERENCES

1. Blackadar, A. K. et al., "Flux of Heat and Momentum in the Planetary Boundary Layer of the Atmosphere," The Pennsylvania State University Mineral Industries Experiment Station, Dept. of Meteorology, Report AFCRL Contract No. AF99604)-6641.
2. Pandolfo, J. P., "Wind and Temperature Profiles for Constant-Flux Boundary Layers in Lapse Conditions with a Variable Eddy Conductivity to Eddy Viscosity Ratio," J. Atmos. Sci., 23, 495-502, 1966.
3. Lumley, J. L. and H. A. Panofsky, The Structure of Atmospheric Turbulence, Interscience Publishers, John Wiley & Sons, New York, 239 pp., 1964.
4. Fichtl, G. H. and G. E. McVehil, "Longitudinal and Lateral Spectra of Turbulence in the Atmospheric Boundary Layer at the Kennedy Space Center," J. Appl. Meteor., 9, 51-63, 1970.
5. Kaufman, J. W. and L. F. Keene, "NASA's 150-meter Meteorological Tower Located at the Kennedy Space Center, Florida," NASA TM X-53699, 1968.
6. Blackadar, A. K. and H. Tennekes, "Asymptotic Similarity in Neutral Barotropic Planetary Boundary Layers," J. Atmos. Sci., 25, 1015-1020, 1968.
7. Langhaar, H. L., "Dimensional Analysis and Theory of Models," John Wiley and Sons, New York, 166 pp., 1951.
8. Panofsky, H. A., "Spectra of the Horizontal Wind Components," NASA Contractor Report NASA CR-1410, 69-83, 1969.
9. Panofsky, H. A. and V. Mirabella, "Estimation of Variances," to be published as a NASA CR, 1970, 56-70.


APPROVAL


STANDARD DEVIATION OF VERTICAL WIND SHEAR IN THE LOWER ATMOSPHERE

by George H. Fichtl

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.

  
W. W. Vaughan  
Chief, Aerospace Environment Division

  
John F. Kaufman, Chief,  
Atmospheric Dynamics Branch

  
E. D. Geissler  
Director, Aero-Astrodynamic Laboratory

DISTRIBUTION

DIR  
DEP-T  
A&TS-PAT  
PM-PR-M, Mr. Goldston  
A&TS-MS-H  
A&TS-MS-IP  
A&TS-MS-IL (8)  
A&TS-TU, Mr. Wiggins (6)

PM-MO-MGR  
Dr. Speer

S&E-R  
Dr. Johnson

AD-S  
Dr. Stuhlinger

S&E-ASTN  
Mr. Heimburg  
Mr. Kroll  
Mr. Hunt  
Mr. Showers  
Mr. Moore  
Mr. Stevens

S&E-COMP  
Dr. Hoelzer  
Mrs. McAllister  
Mr. C. Houston (2)

PD-DIR  
Dr. Lucas  
Mr. E. Goerner

S&E-ASTR  
Mr. Mink  
Mr. Hosenthien  
Mr. B. Moore

S&E-CSE  
Dr. Haeussermann  
Mr. Blackstone

S&E-AERO  
Dr. Geissler  
Mr. Horn  
Mr. Dahm  
Mr. Holderer  
Mr. Reed  
Mr. Craighead  
Mr. Rheinfurth  
Mr. Ryan (2)  
Mr. T. Deaton  
Mr. Lindberg  
Mr. Stone  
Mr. Baker  
Mr. Blair  
Mr. Redus  
Mr. Sims  
Dr. Lovingood  
Mr. Cremin  
Mr. Murphree  
Mr. C. Brown  
Mr. Daniels  
Mr. Kaufman (2)  
Mr. Fichtl (25)  
Mr. O. Smith  
Mr. R. Smith  
Mr. W. Vaughan (3)  
Mr. Turner  
Mr. Camp  
Mr. Susko  
Mr. Hill (3)  
Mrs. Alexander  
Mr. MacKiernan  
Mr. Nelson  
Mr. Huffaker  
Mrs. Hightower  
Mr. E. Weaver

NASA-Kennedy Space Center  
Kennedy Space Center, FL 32931  
Attn: Dr. Bruns  
Mr. M. Preston  
Mr. R. Clark  
Library (2)  
Mr. James Speers

Sci. & Tech. Info. Facility (25)  
P. O. Box 33  
College Park, Md. 20740  
Attn: NASA Rep. (S-AK/RKT)

NASA-Langley Research Center  
Langley Field, Va.  
Attn: Mr. W. Reed, III  
Mr. R. Steiner  
Mr. H. Runyun  
Mr. H. Tolefson  
Mr. V. Alley  
Library (2)

NASA-Lewis Research Center  
21000 Brookpark Rd.  
Cleveland, Ohio 44135  
Attn: Mr. J. C. Estes  
Library (2)

NASA-Manned Spacecraft Center  
Houston, Texas 77001  
Attn: Mr. D. Wade (2)  
Mr. A. Mackey  
Library (2)

NASA-Headquarters  
Ofc. of Adv. Res. & Tech.  
Washington, D. C. 20546  
Attn: Mr. M. Ames  
Mr. D. Michael  
Mr. W. McGowin (4)  
Mr. M. Charak  
Mr. Tischler

NASA-Flight Research Center  
Box 273  
Edwards AFB, Calif. 93523  
Attn: Director  
Mr. L. J. Ehernberger  
Library (2)

NASA Hdqs.  
Dir. Ofc. of Space Sci. & Appl.  
Washington, D. C. 20546  
Attn: Dr. Morris Tepper

NASA-Goddard Space Flight Center  
Greenbelt, Md. 20771  
Attn: Library (2)

NASA-Ames Res. Center  
Moffett Field, Calif. 94035  
Attn: Library (2)

NASA-Wallops Sta.  
Wallops Island, Va.  
Attn: Library (2)

NASA-Hdqs.  
Ofc. of Manned Space Flight  
Washington, D. C. 20546  
Attn: Mr. D. Myers  
Mr. D. Day (2)  
Mr. C. Gay

Aerospace Corp.  
Box 95085  
Los Angeles, Calif. 90045  
Attn: Mr. R. Hemden  
Mr. D. Hargis

Lockheed Missiles & Space Co.  
599 N. Mathilda Ave.  
Sunnyvale, Calif. 94088  
Attn: Dr. S. Adelfang  
Mr. C. Van der Moss

Lockheed Missiles and Space Co.  
Huntsville  
Res. & Engineering Center  
4800 Bradford Blvd.  
Huntsville, Ala. 35806  
Attn: Mr. R. DeMandel  
Mr. S. Krivo

Boeing Scientific Res. Lab.  
P. O. Box 3981  
Seattle, Wash. 98124  
Attn: Dr. Pao  
Library

The Boeing Co., Huntsville  
220 Wynn Dr.  
Huntsville, Ala. 35806  
Attn: Library

General Dynamics  
5873 Kearny Villa Rd.  
San Diego, Calif.  
Attn: Mr. F. Martin  
Library

North American Aviation, Inc.  
Space & Info. Systems Div.  
12214 Lakewood Blvd.

Attn: Mr. C. D. Martin  
Mr. R. Lassen  
Library (2)

McDonald-Douglas  
Adv. Res. Labs.  
5251 Bolsa Ave.  
Huntington Beach, Calif. 92646

Attn: Mr. J. Kelley  
Library (2)

Grumman Aircraft Engr. Corp.  
Bethpage, L. I., N. Y. 11714  
Attn: Library (2)

Martin-Marietta Corp.  
Aerospace Div.  
P. O. Box 179  
Denver 1, Col.  
Attn: Mr. J. M. Bidwell  
Library (2)

Bellcomm, Inc.  
1100 17th St. N. W.  
Washington, D. C. 20036  
Attn: Library (2)

Commander  
Hdqs., Air Weather Service  
Scott AFB, Ill. 62225  
Attn: Library (2)

Air Force Cambridge Res. Labs.  
Bedford, Mass. 01730  
Attn: Dr. H. Ohersten  
Tech. Library (5)  
Mr. N. Sissenwine (2)

Commander Base Weather Station (3)  
AFETR  
Patrick AFB, Fla. 32925

Air Force Flight Dynamics Lab.  
Air Force Systems Command  
Wright-Patterson AFB, Ohio  
Attn: Mr. G. Muller  
Mr. N. Loving (2)  
Library

Atmospheric Sciences Lab. (2)  
U. S. Army Electronics Command  
White Sands Missile Range, New Mexico 88002

U. S. Army Missile Command  
Redstone Arsenal, Ala.  
Attn: Dr. O. Essenwanger  
Dr. O. Stewart  
Library

Commanding General  
U. S. Army Electronics Command  
Ft. Monmouth, N. J. 07703

Meteorology Division (2)  
U. S. Army Dugway Proving Ground  
Dugway, Utah 84022

Chief of Naval Res.  
Dept. of the Navy  
Washington, D. C. 20325

College of Earth & Mineral Sciences  
Pa. State Univ.  
University Park, Pa. 16802  
Attn: Dr. H. Panofsky  
Dr. J. Dutton  
Dr. H. Tennekes  
Dr. A. Blackadar

Dept. of Oceanography and Meteorology  
Texas A&M University  
College Sta. Texas 77840  
Attn: Dr. J. Scoggins

Dept. of Meteorology  
Univ. of Utah  
Salt Lake City, Utah 84116

Director  
Meteorology Dept.  
Univ. of Wash.  
Seattle, Wash. 99703

Dept. of Atmospheric Sciences  
Colorado State Univ.  
Ft. Collins, Colorado 80521  
Attn: Dr. E. Reiter

Dept. of Atmospheric Sciences  
Oregon State University  
Corvallis, Oregon 97330

Meteorology Dept.  
Fla. State Univ.  
Tallahassee, Fla. 32301  
Attn: Dr. Gleeson  
Dr. Hess

Meteorology Dept.  
New York Univ.  
University Heights  
New York, N. Y. 10001

Dept. of Earth Sciences  
University of Ala. Huntsville  
4701 University Drive 35805  
Attn: Dr. J. Branerd  
Dr. Shih

Dept. of Geosciences  
Purdue Univ.  
LaFayette, Ind. 47907  
Attn: Dr. Phil Smith

American Meteorological Society  
45 Beacon St.  
Boston, Mass. 02108

Federal Aviation Agency (3)  
Washington, D. C. 20546

National Center for Atmospheric Res.  
Laboratory of Atmospheric Sci.  
Boulder, Colorado 80302  
Attn: Library (2)